

154884 COOLTOPPER SINGLE POST PYRAMID ROOF DB ONLY  
 NOTE: THE COOLTOPPER SINGLE POST IS NOT-IPEMA CERTIFIED.

170894 SWAY FUN (12" HEIGHT)

191031 CURB FOR ACCESSIBLE PANEL

115243 SOUND CHIMES PANEL

116244 PIPE BARRIER

168110 12' DOUBLE WIDE RAMP W/GUARDRAILS AND CURBS

168546 RAMP EXIT PLATE TO GRADE  
 \*CP000163 DTR PB STEEL FLUSH POST AT GRADE W/D-CAP

154752 HEX DECK EXTENSION

191031 CURB FOR ACCESSIBLE PANEL

164092 BONGO PANEL

116244 PIPE BARRIER

NOTE: MAX SLOPE IS 1:12 (4.76') PER ADA


PlayBooster®  
(2-12 years)

Max Fall Height: 12 inches

TOTAL SQUARE FOOTAGE  
728 SQ.FT.

TOTAL ELEVATED PLAY COMPONENTS	3	REQUIRED	3
TOTAL ELEVATED COMPONENTS ACCESSIBLE BY RAMP	3	REQUIRED	3
TOTAL ELEVATED COMPONENTS ACCESSIBLE BY TRANSFER	0	REQUIRED	0
TOTAL ACCESSIBLE GROUND LEVEL COMPONENTS SHOWN	0	REQUIRED	0
TOTAL DIFFERENT TYPES OF GROUND LEVEL COMPONENTS	0	REQUIRED	0

Estimated manufacturing time:  
6 weeks from the time of LSI order acceptance, or receipt of SkyWays release of fabrication form if applicable.



Design  
3879

Landscape  
Structures

SYSTEM TYPE:  
Playbooster  
  
DRAWING #:  
3879



The play components identified on this plan are IPEMA certified. (Unless model number is preceded with \*) The use and layout of these components conform to the requirements of ASTM F1487. To verify product certification, visit [www.ipema.org](http://www.ipema.org)

THIS PLAY AREA & PLAY EQUIPMENT IS DESIGNED FOR AGES 2-12 YEARS UNLESS OTHERWISE NOTED ON PLAN.

IT IS THE MANUFACTURERS OPINION THAT THIS PLAY AREA DOES CONFORM TO THE A.D.A. ACCESSIBILITY STANDARDS, ASSUMING AN ACCESSIBLE PROTECTIVE SURFACING IS PROVIDED, AS INDICATED, OR WITHIN THE ENTIRE USE ZONE.

THIS CONCEPTUAL PLAN WAS BASED ON INFORMATION AVAILABLE TO US. PRIOR TO CONSTRUCTION, DETAILED SITE INFORMATION INCLUDING SITE DIMENSIONS, TOPOGRAPHY, EXISTING UTILITIES, SOIL CONDITIONS, AND DRAINAGE SOLUTIONS SHOULD BE OBTAINED, EVALUATED, & UTILIZED IN THE FINAL DESIGN. PLEASE VERIFY ALL DIMENSIONS OF PLAY AREA, SIZE, ORIENTATION, AND LOCATION OF ALL EXISTING UTILITIES, EQUIPMENT, AND SITE FURNISHINGS PRIOR TO ORDERING. SLIDES SHOULD NOT FACE THE HOT AFTERNOON SUN.

CHOOSE A PROTECTIVE SURFACING MATERIAL THAT HAS A CRITICAL HEIGHT VALUE TO MEET THE MAXIMUM FALL HEIGHT FOR THE EQUIPMENT (REF. ASTM F1487 STANDARD CONSUMER SAFETY PERFORMANCE SPECIFICATION FOR PLAYGROUND EQUIPMENT FOR PUBLIC USE, SECTION 8 CURRENT REVISION). THE SUBSURFACE MUST BE WELL DRAINED. IF THE SOIL DOES NOT DRAIN NATURALLY IT MUST BE TILED OR SLOPED 1/8" TO 1/4" PER FOOT TO A STORM SEWER OR A "FRENCH DRAIN".

DESIGNED BY:

COPYRIGHT: 5/30/19  
 LANDSCAPE STRUCTURES, INC.  
 601 7th STREET SOUTH - P.O. BOX 198  
 DELANO, MINNESOTA 55328  
 PH: 1-800-328-0035 FAX: 1-763-972-6091

Date	Previous Drawing #	Initials