


Smart Play®
(2-5 years)

Max Fall Height: 44 inches



Smart Play®
(6-23 months)

Max Fall Height: 7 inches


IT IS THE MANUFACTURERS OPINION AND
INTENT THAT THE USE AND LAYOUT OF THESE
COMPONENTS CONFORM TO THE AMERICAN
SOCIETY FOR TESTING AND MATERIALS (ASTM)
STANDARD ASTM F2373

*FENCE BY OTHERS-
PER ASTM F2373-11

11.9.2.1 It is recommended that outdoor play areas with unlimited
access be located within fenced and gated areas.

2-5 AREA

TOTAL ELEVATED PLAY COMPONENTS	5		
TOTAL ELEVATED COMPONENTS ACCESSIBLE BY RAMP	0	REQUIRED	0
TOTAL ELEVATED COMPONENTS ACCESSIBLE BY TRANSFER	5	REQUIRED	3
TOTAL ACCESSIBLE GROUND LEVEL COMPONENTS SHOWN	7	REQUIRED	2
TOTAL DIFFERENT TYPES OF GROUND LEVEL COMPONENTS	5	REQUIRED	5



Loft and Nook

Landscape
Structures

SYSTEM TYPE:
SmartPlay

DRAWING #:



landscape
structures



The play components identified on this plan
are IPEMA certified. (Unless model number
is preceded with *) The use and layout of
these components conform to the
requirements of ASTM F1487. To verify
product certification, visit www.ipema.org

IT IS THE MANUFACTURERS OPINION AND
INTENT THAT THE USE AND LAYOUT OF THESE
COMPONENTS CONFORM TO THE AMERICAN
SOCIETY FOR TESTING AND MATERIALS (ASTM)
STANDARD ASTM F2373

THIS PLAY AREA & PLAY EQUIPMENT IS
DESIGNED FOR AGES 6-60 MONTHS
UNLESS OTHERWISE NOTED ON PLAN.

IT IS THE MANUFACTURERS OPINION THAT
THIS PLAY AREA DOES CONFORM TO
THE A.D.A. ACCESSIBILITY STANDARDS,
ASSUMING AN ACCESSIBLE PROTECTIVE
SURFACING IS PROVIDED, AS INDICATED, OR
WITHIN THE ENTIRE USE ZONE.

THIS CONCEPTUAL PLAN WAS BASED ON
INFORMATION AVAILABLE TO US. PRIOR TO
CONSTRUCTION, DETAILED SITE INFORMATION
INCLUDING SITE DIMENSIONS, TOPOGRAPHY, EXISTING
UTILITIES, SOIL CONDITIONS, AND DRAINAGE
SOLUTIONS SHOULD BE OBTAINED, EVALUATED, &
UTILIZED IN THE FINAL DESIGN. PLEASE VERIFY ALL
DIMENSIONS OF PLAY AREA, SIZE, ORIENTATION, AND
LOCATION OF ALL EXISTING UTILITIES, EQUIPMENT,
AND SITE FURNISHINGS PRIOR TO ORDERING. SLIDES
SHOULD NOT FACE THE HOT AFTERNOON SUN.

CHOOSE A PROTECTIVE SURFACING MATERIAL THAT
HAS A CRITICAL HEIGHT VALUE TO MEET THE
MAXIMUM FALL HEIGHT FOR THE EQUIPMENT (REF.
ASTM F1487 STANDARD CONSUMER SAFETY
PERFORMANCE SPECIFICATION FOR PLAYGROUND
EQUIPMENT FOR PUBLIC USE, SECTION 8 CURRENT
REVISION). THE SUBSURFACE MUST BE WELL
DRAINED. IF THE SOIL DOES NOT DRAIN NATURALLY
IT MUST BE TILED OR SLOPED 1/8" TO 1/4" PER
FOOT TO A STORM SEWER OR A "FRENCH DRAIN".

DESIGNED BY:

COPYRIGHT: 10/7/21
LANDSCAPE STRUCTURES, INC.
601 7th STREET SOUTH - P.O. BOX 198
DELANO, MINNESOTA 55328
PH: 1-800-328-0035 FAX: 1-763-972-6091

Date	Previous Drawing #	Initials